

CLAIMS

1. A layered structure comprising
 - a first intermediate layer, said first intermediate layer
5 comprising at least one element of group IVB, group VB or group VIB;
 - a second intermediate layer deposited on top of said first intermediate layer, said second intermediate layer comprising a diamond-like nanocomposite composition;
 - 10 - a diamond-like carbon layer deposited on top of said second intermediate layer.
2. A layered structure according to claim 1, whereby said first intermediate layer comprises titanium and/or chromium.
15
3. A layered structure according to claim 1 or 2, whereby said structure further comprises at least a layer comprising a diamond-like nanocomposite composition on top of said diamond-like carbon layer.
20
4. A layered structure according to any one of the preceding claims, whereby said first intermediate layer has a thickness between 0.001 and 1 μm .
- 25 5. A layered structure according to any one of the preceding claims, whereby said second intermediate layer has a thickness of 0.01 to 5 μm .
- 30 6. A layered structure according to any one of the preceding claims, whereby said diamond-like carbon layer has a thickness between 0.1 and 10 μm .
7. A layered structure according to any one of the preceding claims, whereby said nanocomposite composition comprises in

-11-

proportion to the sum of C, Si, and O in at% 40 to 90 % C, 5 to 40 % Si, and 5 to 25 % O.

- 5 8. A layered structure according to any one of the preceding claims, whereby said second intermediate layer comprises a metal doped diamond-like nanocomposite composition.
- 10 9. A layered structure according to any one of the preceding claims, whereby said diamond-like carbon layer is doped with a metal.
- 10 10. A substrate covered at least partially with a layered structure according to any one of claims 1 to 9.
- 15 11. The use of a substrate according to claim 10 for high shear and/or high impact applications.
- 20 12. A method to cover a substrate with a layered structure according to any one of claims 1 to 10, whereby said method comprises the steps of
- 20 - providing a substrate;
- applying a first intermediate layer, said first intermediate layer comprising at least one element of group IVB, group VB or group VIB;
- 25 - applying a second intermediate layer, said second intermediate layer comprising a diamond-like nanocomposite composition;
- applying a diamond-like carbon layer.